

Product Specifications

Specifications	ESTEAM®	J-1®	J-2®	J-2000®	J-4000®
Voltage (120V)	✓	✓	✓	✓	✓
Voltage (230V)	✓	✓	✓	✓	✓
Wattage	600W (120V) 625W (230V)	1300W	1300W	1300W	1500W
Amps (120V)	5	10.83	10.83	10.83	12.5
Amps (230V)	2.71	5.65	5.65	5.65	6.52
Fusible Link Safety Fuse	✓	✓	✓	✓	✓
Power Cord Length	8 feet	7 feet	7 feet	7 feet	7 feet
Multiple Cord Plug Configurations Available	✓	✓	✓	✓	✓
High Temperature Silicone Braided Wiring	✓	✓	✓	✓	✓
Electrical Certifications (Both 120V & 230V)	UL, cUL, CE, NOM, ANCE, TUV	UL, cUL, CE, NOM, ANCE, TUV	UL, cUL, CE, NOM, ANCE, TUV	UL, cUL, CE, NOM, ANCE, TUV	UL, cUL, CE, NOM, ANCE, TUV
Uses Ordinary Tap or Distilled Water	✓	✓	✓	✓	✓
Water Capacity	8 ounces	1 gallon	1 gallon	.75 gallon	1 gallon
Water Level Easily Viewed	✓	✓	✓	✓	✓
Pre-Heat Time with Maximum Water	2 minutes	2 minutes	2 minutes	2 minutes	15 minutes
Steam Duration	16 minutes	2 hours	2 hours	1.5 hours	2 hours
Hose Length	—	—	5.5 feet	5.5 feet	5.5 or 7.5 feet
Stainless Steel Boiler Tank	—	—	—	—	✓
Heating Element Type	Die Cast in Aluminum	Die Cast in Brass	Die Cast in Brass	Die Cast in Brass	Incoloy
Die Cast Aluminum Housing	—	✓	✓	—	✓
Hose/Clothing Hanger	—	—	✓	✓	✓
3 Year Limited Warranty	✓	✓	✓	✓	✓
Made in the U.S.A.	✓	✓	✓	✓	✓
Net Weight Assembled	2 pounds	12 pounds	15 pounds	14 pounds	22 pounds
Gross Package Weight	3 pounds	15 pounds	17 pounds	18 pounds	26 pounds
Assembled Dimensions (L x W x H)	5.75" x 3" x 6.5"	13.5" x 7.5" x 13"	13.5" x 7.5" x 64.5"	15" x 10" x 64"	19.5" x 10.5" x 62"
Single Carton Dimensions (L x W x H)	11" x 5" x 6.5"	15" x 9" x 19"	15" x 9" x 19"	18" x 11.5" x 15"	20" x 12" x 13.5"
Attachments Available A - Auto B - Steam Brush C - Carpet D - Drapery DM - Metal Head Drapery H - Hat i - Interchangeable M - Metal Head W - Wig	Voltage Converter (converts 230V to 120V)	H	B, H, i, M, W	B, H, i, M, W	A, B, C, D, DM, H, i, M, W